



SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 5.1

SDS Revision Date: 6/25/2015

1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	DEOXIT® Gold G-SERIES, 5% MINI-SPRAY, (P/N GN5MS-15), 14 grams, VOC Compliant
1.2	Chemical Name:	NA
1.3	Synonyms:	DeoxIT® Gold G-Series 5% Spray; PN GN5MS-15
1.4	Trade Names:	DeoxIT® Gold G-Series 5% Spray; PN GN5MS-15
1.5	Product Uses & Restrictions:	Conditioner, enhancer for plated and gold plated electronic contacts & connectors
1.6	Distributor's Name:	CAIG Laboratories, Inc.
1.7	Distributor's Address:	12200 Thatcher Court, Poway, CA 92064-6876 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN XXXXX)
1.9	Business Phone / Fax:	+1 (800) 224-4123

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). DANGER! PRESSURIZED CONTAINER; MAY BURST IF HEATED. EXTREMELY FLAMMABLE GAS. Classification: Aerosols 1, Flam. Gas 1 Hazard Statements (H): H229 – Pressurized container; may burst if heated. Precautionary Statements (P): P210 – Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P251 – Do not pierce or burn, even after use. P410P412 – Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F P332+P313 – If skin irritation occurs: get medical advice/attention. P377 – Leaking gas fire: Don not extinguish, unless leak can be stopped safely. P381 – In case of leakage, eliminate all ignition sources. P403 – Store in a well-ventilated place. P405 – Store locked up. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).</p>	
-----	------------------------	---	--

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					ppm		ppm			ppm				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
1,1,1,3,3-PENTAFLUORPROPANE	460-73-1	NA	419-170-6	60-100	300	NA	NF	NF	NF	NA	NA	NA		
ISOBUTANE	75-28-5	TZ4300000	200-857-2	10-30	600	750	NF	NF	NF	NA	NA	NA		
DEOXIT® Gold G-SERIES, G100L	NA	NA	NA	3-7	NA	NA	NF	NF	NF	NA	NA	NA		


4. FIRST AID MEASURES

4.1	First Aid:	<p>Ingestion: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p>Eyes: Splashes are not likely; however, mist may cause irritation. If product gets in the eyes may cause irritation; flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally. If irritation persists repeat flushing. Get medical attention.</p> <p>Skin: Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Treat for frostbite if necessary, be gently warming affected area. If irritation, redness or swelling persists, contact a physician immediately.</p> <p>Inhalation: Remove victim to fresh air at once. If breathing difficult, administer oxygen. Gross overexposure may cause central nervous system depression, dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping," apprehension, light-headedness, weakness, fainting, loss of consciousness, and death.</p>
4.2	Effects of Exposure:	<p>Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea.</p> <p>Eyes: Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p>Skin: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p>Inhalation: Gross overexposure may cause central nervous system depression, dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping," apprehension, light-headedness, weakness, fainting, loss of consciousness, and death.</p>

4. FIRST AID MEASURES – cont'd

4.3	Symptoms of Overexposure:	<p>Ingestion: Nausea, intestinal discomfort, vomiting and/or diarrhea.</p> <p>Eyes: Overexposure in eyes may cause redness, itching and watering.</p> <p>Skin: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals.</p> <p>Inhalation: Gross overexposure may cause central nervous system depression, dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping," apprehension, light-headedness, weakness, fainting, loss of consciousness, and death.</p>											
4.4	Acute Health Effects:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Frostbite like effect to skin.											
4.5	Chronic Health Effects:	Overexposure may trigger asthma-like symptoms in some sensitive individuals. May also induce skin sensitization and respiratory hypersensitivity. Possible allergic dermatitis.											
4.6	Target Organs:	Eyes, Skin, Respiratory System.											
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system).	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #0000FF; color: white;">HEALTH</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: #FF0000; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: #FFA500; color: white;">PHYSICAL HAZARDS</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: #000000; color: white;">PROTECTIVE EQUIPMENT</td> <td style="text-align: center;">B</td> </tr> <tr> <td style="font-size: small;">EYES</td> <td style="font-size: small;">SKIN</td> </tr> </table>	HEALTH	1	FLAMMABILITY	1	PHYSICAL HAZARDS	0	PROTECTIVE EQUIPMENT	B	EYES	SKIN
HEALTH	1												
FLAMMABILITY	1												
PHYSICAL HAZARDS	0												
PROTECTIVE EQUIPMENT	B												
EYES	SKIN												

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	Level 1 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, Hydrogen Fluoride).	
5.2	Extinguishing Methods:	Water, Foam, CO ₂ , Dry Chemical. Use water spray to cool unopened containers.	
5.3	Firefighting Procedures:	Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.	



6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. Plastic or rubber gloves, respirator, eye protection and apron may be required for clean-up of large spills.</p> <p>Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. Do not use water or a material such as "speedy dry" to soak up material. Sweep up material using non-sparking materials (e.g., plastic brooms, shovels, dustpans) and place into a plastic container or plastic liner within another container.</p> <p>Large Spills: Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant.</p>
-----	---------	---

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Do not eat, drink or smoke when handling this product. Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water.
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying keep cap in place when not in use.
7.3	Special Precautions:	Clean all spills promptly.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)	CHEMICAL NAME(S)	ACGIH		NOHSC			OSHA			OTHER
			TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
			ISOBUTANE		600	750	NF	NF	NF	NA	
8.2	Ventilation & Engineering Controls:	General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).									
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.									
8.4	Eye Protection:	Avoid eye contact. None required under normal conditions of use. Safety glasses could be used when handling or using large quantities of this product.									
8.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves.									
8.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 5 lbs), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.									

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Light yellow aerosol spray/mist
9.2	Odor:	Ethereal / hydrocarbon odor
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	15 °C (59 °F) - 1,1,1,3,3-Pentafluoropropane
9.7	Flashpoint:	NA
9.8	Upper/Lower Flammability Limits:	NA
9.9	Vapor Pressure:	50 +/-5 PSIG @ 20 °C
9.10	Vapor Density:	NA
9.11	Relative Density:	0.8
9.12	Solubility:	Not soluble in water
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	412 °C (774 °F) – 1,1,1,3,3-Pentafluoropropane
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	VOC content 268 g/L

10. STABILITY & REACTIVITY

10.1	Stability:	Stable under normal conditions; unstable with heat or contamination.
10.2	Hazardous Decomposition Products:	Change in color signifies exposure to ultraviolet light or exceeding shelf life. Will not degrade to unstable products. Discard solution.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks, high heat, incompatible substances and direct sunlight.
10.5	Incompatible Substances:	Avoid extreme heat and ignition sources. Store away from oxidizers.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product: 1,1,1,3,3-Pentafluoropropane: Acute Dermal (rabbit) – LD ₅₀ > 2,000 mg/kg; Cardiac Sensitization (dogs) – No effects noted at 35,000 ppm, the threshold for induction of cardiac arrhythmias in the presence of injected adrenalin was 44,000 ppm. Acute Inhalation (rat): 4-hr. LC ₅₀ > 200,000 ppm. No lethality at 200,000 ppm. Evidence of transient anesthetic effect. Acute Inhalation (mouse): 4-hr. LC ₅₀ > 100,000 ppm. No lethality at 100,000 ppm. Evidence of transient under activity during exposure.		
11.3	Acute Toxicity:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.		
11.4	Chronic Toxicity:	This material may aggravate any pre-existing skin condition (e.g., dermatitis).		
11.5	Suspected Carcinogen:	No.		



SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 5.1

SDS Revision Date: 6/25/2015

11. TOXICOLOGICAL INFORMATION – cont'd

11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.
11.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.
11.8	Biological Exposure Indices:	NE
11.9	Physician Recommendations:	Treat symptomatically.

12. ECOLOGICAL INFORMATION


12.1	Environmental Stability:	There is no specific data available for this product.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.

13. DISPOSAL CONSIDERATIONS


13.1	Waste Disposal:	Products covered by this MSDS, in their original form, when disposed as waste, are considered non hazardous waste according to Federal RCRA regulations (40 CFR 261). Disposal should be in accordance with local, state and federal regulations. Dispose of in accordance with federal, state and local regulations.
13.2	Special Considerations:	California Waste Code: 331

14. TRANSPORTATION INFORMATION


The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020	
14.2	IATA (AIR):	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L)	
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE"	
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.6	SCT (MEXICO):	UN1950, AEROSOLS, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)	
14.7	ADGR (AUS):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	NA	
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, (Cosmetics).	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List.	

15. REGULATORY INFORMATION – cont'd

15.7	State Regulatory Information:	<u>1,1,1,2-Tetrafluorethane</u> can be found on the following state criteria lists: Minnesota Hazardous Substances List (MN) No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).	
15.8	Other Requirements:	The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: <u>Isobutene</u> : Flammable (F) <u>Risk Phrases</u> : (R) 12 – Extremely flammable. <u>Safety Phrases</u> : (S) 2-9-16 – Keep out of reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking.	



SAFETY DATA SHEET



Page 5 of 6
SDS-E-GN5MS-15

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 5.1

SDS Revision Date: 6/25/2015

16. OTHER INFORMATION

16.1	Other Information:	DANGER! PRESSURIZED CONTAINER; MAY BURST IF HEATED. EXTREMELY FLAMMABLE GAS. Use only as directed. Keep out of reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/	
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	 <i>Dangerous Goods Training & Consulting</i>

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
----------------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
C	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₀₁	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₁₀, LD₁₀, & LD₀₁ or TC, TC₀₁, LC₁₀, & LC₀₁	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment